



Make up your code

<u>KS</u>	<u>X</u>	<u>08</u>	<u>X</u>	<u>XXX</u>	<u>XX</u>	<u>XXX</u>
Series	1 = concave 2 = convex 3 = plane	LED diameter	N = Natural chrome finish B = Black chrome finish	LED code	Operating Voltage 02* 05 12 24 48	Cable length** (Standard 200 mm)

* not available for BLUE and WHITE

** without cable = Z

LED Code	Material	Wave length (nm) Color	Lens Type	Iv (mcd) @ 20mA		Viewing Angle 2θ
				Min	Typ	
C01	GaAsP/Gap	625/Red	Red Diffused	40	100	120°
C02	GaP	565/Green	Green Diffused	20	60	120°
C03	GaAsP/GaP	590/Yellow	Yellow Diffused	20	50	120°
C04	GaAsP/GaP	625/Orange	Orange Diffused	40	100	120°
C05	GaAsP/GaP	625/Red	White diffused	30	80	100°
Bicolor	GaP	565/Green		20	50	

All models listed in this page are referred to the SUPER-STANDARD series only.

We can supply you with custom devices in a short time and at competitive prices as follows:

- ◆ 3.000 to 10.000 pcs by no. 4CNC lathes
- ◆ More than 10.000 pcs by no. 30 lathes with sliding headstock.

Therefore on your request we can realize any device on the grounds of your drawing with any material: metal & plastic.

