




PLL080425 - IESNA Type II







KGAS13 - Gasket for PLL08xxx



KGAS13 - Physical Characteristics

Hardness sh A : 65 +/-5	Color:	Transparent	Abbrev. : SIL 65H TRASP	
Basic Element : VMQ	Vulcan	ization: 10min @ 150°C	Annealing : 4 ore@200°C	
Original Parameters	Unit of Measure	Detected Value	s Test Method	
Hardness	Shore A	65	ASTM D 2240	
Hardness	IRHD			
100% Modulus	MPa		ASTM D 412	
100% Modulus	N/mm²			
Tensile strenght	MPa	9	ASTM D 412	
Elongation	%	620	ASTM D 412	
Tear resistance	N/mm	30	ASTM D 624/B	
Specific Gravity	g/cm ³	1.16	ASTM D 297	
Brittleness Point	°C			
TR-TEST TR10	°C		ASTM D 1329	
TR TEST TR-30	°C			
Compression Set 25%				
Temperature: 175°C @ 22h	%	27	ASTM D 395/B	



Materials

Material	Тор			
PMMA 8N **	-40°90°C			
For further information please visit Evonik website				

**

PLL080XXX series is made of the same material used to produce PLEXIGLAS® Solar which guarantees it will show no yellowing for 10 years.

Yellowness Index (YI) according to the test standards for Arizona/Florida outdoor exposure testing:

- YI 6 under hot/dry conditions
- YI 8 under hot/wet conditions

Notes:

- Intensity (I) and illuminance (E) data are normalized by 1000 lm
- The optical values shown are the result of optical simulations carried out with LIGHTOOLS, ASAP and ZEMAX software systems. The optical simulations are carried out on the basis of the typical values provided in the LED manufacturers' official datasheets. The photometric analysis has been carried out on physical samples. On request, by supplying your PCB, we can provide the measurement photometric file.

Use and Maintenance

- DO NOT HANDLE OR INSTALL LENSES WITHOUT WEARING GLOVES, SKIN OILS MAY DAMAGE LENS OR LIGHT TRANSMISSION;
- CLEAN LENSES WITH MILD SOAP AND WATER AND A SOFT CLOTH;
- DO NOT USE ANY COMMERCIAL CLEANING SOLVENTS ON LENSES.

Disclaimer

Please note that flow lines and weld lines on the external surfaces of the lenses are acceptable if the optical performance of the lens is within the specifications.

Should you require further information, please contact Khatod for advice. All lens testing must be subject to identical conditions as Khatod test condition. Khatod Optoelectronic, Milan, Italy, manufactures lenses for LEDs. Any other use of the lens shall void our liability and warranty. The lenses are an inert component to be used in the manufacture of various products. Our warranty and liability are limited only to the manufacture of the lens. You may not modify, copy, distribute reproduce, license or alter the lens and related materials of Khatod. Khatod does not warrant against damages or defects arising out of the use or misuse of the products; against defects or damage arising from improper installation, or against defects in the product or in its components. No warranty of any kind, expressed or implied, is made regarding the safety of the products. The entire risk as to the quality or performance of the product is with the buyer. In no event shall Khatod be liable for any direct, indirect, punitive, incidental, special, consequential damages, or any damages whatsoever arising out of or connected with the use or misuse of the product. Khatod shall not have any obligation with respect to the product or any part thereof, whether based on contract, tort, strict liability or otherwise. Buyer assumes all risks and liability from use of the product. The laws of Milan, Italy govern this product warranty and liability and you hereby consent to the exclusive jurisdiction and venue of courts in Milan, Italy in all disputes arising out of or relating to the use of this product. Production, marketing, distribution, sale of these products as well as their possible modifications and variations are only exclusive right of Khatod Optoelectronic. No company can perform any of these actions without written permission released by Khatod Optoelectronic. The information contained in this document is proprietary of Khatod Optoelectronic and may change without notice.